

Serial No. 10/646,596

Page 2 of 8

JUL 11 2007

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1 1. (original) A communication system for transporting Internet protocol-formatted
2 communications over a Universal Mobile Telecommunications System (UMTS) wireless
3 communications system, the communication system including a base station and a radio network
4 controller, the communication system further comprising:

5 an inter-working gateway adapted for interconnection to the radio network controller and
6 the base station, the inter-working gateway being adapted to communicate via Internet transport
7 protocols and UMTS-based transport protocols, the inter-working gateway being further adapted
8 to reformat communications with movable UMTS-based radio-controlled network layer
9 protocols for transport to the radio network controller and to reformat communications with
10 movable Internet radio-controlled network layer protocols for transport to the base station.

1 2. (original) The communications system as recited in claim 1, wherein the UMTS
2 communications system exists at an installed site.

1 3. (original) The communications system as recited in claim 1, wherein the inter-
2 working gateway is supplied as pre-installed with the transport protocols.

1 4. (original) The communications system as recited in claim 1, wherein the inter-
2 working gateway is adapted to receive and download the radio-controlled network layer
3 protocols and the transport protocols from the base station.

1 5. (original) The communications system as recited in claim 1, wherein the base
2 station and the inter-working gateway are interconnected in a local area network.

1 6. (original) The communications system as recited in claim 1, further comprising:

2 an SDRAM memory;

3 one or more channel elements, each comprising a digital signal processor and associated
4 flash memory and an application specific integrated circuit to manage baseband processing; and

5 a microprocessor for configuring each channel element, storing user data in the SDRAM
6 memory, and exchanging user data with the digital signal processor.

Serial No. 10/618,880

Page 3 of 8

1 7. (original) The communications system as recited in claim 1, wherein an
2 interconnection of the inter-working gateway with the base station carries the communications
3 reformatted with the movable UMTS-based radio-controlled network layer protocols in a first
4 direction, and the communications reformatted with the movable Internet radio-controlled
5 network layer protocols in a second direction.

1 8. (original) The communications system as recited in claim 1, wherein an
2 interconnection of the inter-working gateway with the radio network controller carries the
3 communications reformatted with the movable UMTS-based radio-controlled network layer
4 protocols in a first direction, and the communications reformatted with the movable Internet
5 radio-controlled network layer protocols in a second direction.

1 9. (original) The communications system as recited in claim 1, wherein
2 an interconnection of the inter-working gateway with the base station carries the
3 communications reformatted with the movable UMTS-based radio-controlled network layer
4 protocols in a first direction, and the communications reformatted with the movable Internet
5 radio-controlled network layer protocols in a second direction, and
6 an interconnection of the inter-working gateway with the radio network controller carries
7 the communications reformatted with the movable UMTS-based radio-controlled network layer
8 protocols in a first direction, and the communications formatted with the movable Internet radio-
9 controlled network layer protocols in a second direction.

1 10. (original) The communications system as recited in claim 1, further comprising:
2 a Node-B base station adapted for transmitting and receiving cellular telephone
3 communications, the Node-B base station being interconnected with the radio network controller
4 for exchanging wireless cellular telephone communications.

1 11. (original) The communications system as recited in claim 10, wherein the UMTS
2 communications system exists at an installed site.

1 12. (original) The communications system as recited in claim 10, wherein the inter-
2 working gateway is supplied as pre-installed with the transport protocols.

1 13. (original) The communications system as recited in claim 10, wherein the inter-
2 working gateway is adapted to receive and download the radio-controlled network layer
3 protocols and the transport protocols from the base station.

584428-1

Serial No. 10/618,880

Page 4 of 8

1 14. (original) The communications system as recited in claim 10, wherein the base
2 station and the inter-working gateway are interconnected in a local area network.

1 15. (original) The communications system as recited in claim 10, further comprising:
2 an SDRAM memory;
3 one or more channel elements each comprising, a digital signal processor and associated
4 flash memory and an application specific integrated circuit to manage baseband processing; and
5 a microprocessor for configuring each channel element, storing user data in the SDRAM
6 memory, exchanging user data with the digital signal processor, and processing the movable
7 protocols.

1 16. (original) The communications system as recited in claim 10, wherein an
2 interconnection of the inter-working gateway with the base station carries the communications
3 reformatted with the movable UMTS-based radio-controlled network layer protocols in a first
4 direction, and the communications reformatted with the movable Internet radio-controlled
5 network layer protocols in a second direction.

1 17. (original) The communications system as recited in claim 10, wherein an
2 interconnection of the inter-working gateway with the radio network controller carries the
3 communications reformatted with the movable UMTS-based radio-controlled network layer
4 protocols in a first direction, and the communications reformatted with the movable Internet
5 radio-controlled network layer protocols in a second direction.

1 18. (original) The communications system as recited in claim 10, wherein
2 an interconnection of the inter-working gateway with the base station carries the
3 communications reformatted with the movable UMTS-based radio-controlled network layer
4 protocols in a first direction, and the communications reformatted with the movable Internet
5 radio-controlled network layer protocols in a second direction, and

6 an interconnection of the inter-working gateway with the radio network controller carries
7 the communications reformatted with the movable UMTS-based radio-controlled network layer
8 protocols in a first direction, and the communications reformatted with the movable Internet
9 radio-controlled network layer protocols in a second direction.

1 19. (original) An inter-working gateway for wirelessly transporting Internet protocol-
2 formatted communications in a Universal Mobile Telecommunications System (UMTS)
3 communications system, the inter-working gateway comprising:

584428-1

Serial No. 10/618,880

Page 5 of 8

4 means for communicating via Internet transport protocols and UMTS-based transport
5 protocols;

6 means for reformatting communications using movable UMTS-based transport protocols
7 for transport to a radio network controller; and

8 means for reformatting communications using movable Internet radio-controlled network
9 layer protocols from the radio network controller to the inter-working gateway.

10 20. (withdrawn) A method for transporting Internet protocol-formatted
11 communications over a Universal Mobile Telecommunications System (UMTS) wireless
12 communications system, the method comprising:

13 segmenting Internet-formatted communications into Internet framing protocol-protocol
14 data units (FP-PDUs);

15 multiplexing the FP-PDUs over separate label switched paths via multiple protocol label
16 switching (MPLS); and

17 exchanging the multiplexed FP-PDUs as formatted multiplexed MPLS data segments
18 between a base station and a radio network controller.

19 21. (withdrawn) The method as recited in claim 20, further comprising:
20 installing radio-controlled network protocols in an inter-working gateway interconnected
21 between the base station and the radio network controller.

1 22. (withdrawn) The method as recited in claim 20, further comprising:
2 segmenting the Internet-formatted communications into FP-PDUs of 350 octets
3 maximum length.

1 23. (withdrawn) The method as recited in claim 20, further comprising:
2 formatting the FP-PDUs with UMTS radio-controlled network layer protocols for
3 transport in the UMTS wireless communications system; and

4 formatting the FP-PDUs with Internet radio-controlled network layer protocols for
5 transmission as wireless Internet communications.

24. (withdrawn) The method as recited in claim 21, further comprising:
transporting the FP-PDUs formatted with UMTS radio-controlled network layer
protocols from the base station in a first direction; and

Serial No. 10/618,880

Page 6 of 8

transporting the FP-PDUs formatted with Internet radio-controlled network layer protocols in a second direction.

25. (original) A method for transporting Internet protocol-formatted communications over a Universal Mobile Telecommunications System (UMTS) wireless communications system, the UMTS communication system including a base station and a radio network controller, the communication system comprising:

reformatting communications using movable UMTS-based radio-controlled network layer protocols for transport between the base station and the radio network controller; and

reformatting communications using movable Internet radio-controlled network layer protocols for transport between the base station and the radio network controller.

584428-2